

6823 Max. 12 W

AC/DC POWER SUPPLIES - LINEAR - REGULATED

6 - 12 V

12 - 24 V

5 V Max. 8 W



tech space

- Trinnløs justerbar utgangsspenning
- Termosikring i transformator
- Nettledning
- Sekundærledning eller snappkontakt
- Kan leveres med festebrakett
- Finnes i flerspenningsversjon +5 ± 12 V
- Stepless adjustable output voltage
- Thermal fuse in transformer
- Mains cord
- Cord or snap terminals
- Mounting bracket available
- Available as a multiple output powersupply +5 ± 12 V



Tekniske data - 6-12 V versjon

Technical specifications - 6-12 V version

Inngangsspenning:	Input voltage:	230 VAC +6/-10%, 50/60Hz
Utgangsspenning:	Output voltage:	6-12 VDC
Maks. utgangseffekt:	Max. output power:	12 W
Maks. laststrøm	Max. load current	
• 6-12 V:	• 6-12 V:	6 V / 0,6 A - 12 V / 1,0 A
• 12-24 V:	• 12-24 V:	0,5 A
Lastregulering:	Load regulation:	130 mV
Temperaturområde:	Temperature range:	-10°C - +40°C
Rippel:	Ripple:	3 mV RMS
Isolasjonsklasse:	Insulation class:	II
Isolasjonsspenning:	Insulation class:	3000 VAC
Elektrisk sikkerhetsstandard:	Electrical safety standard:	EN 60950
EMC standarder	EMC standards	
• Emisjon:	• Emission:	EN 61000-6-3
• Immunitet:	• Immunity:	EN 61000-6-1
Mål (LxBxH):	Dimensions (LxWxH):	98 x 108 x 55 mm
Vekt:	Weight:	920 g

* Visse tekniske data kan variere for de forskjellige spenningsversjoner.

* Some technical specifications may differ for other voltage versions.

Diagram 6-12 V versjon
Diagram 6-12 V version

