


- 4,5-12 V eller 12-30 V justerbar utgangsspenning
- Kompakt enhet, lett vekt (135 g)
- Fast ledning, kan leveres med utskiftbare DC plugger
- Leveres med EU, UK eller AUS nettilkobling
- 4,5-12 V or 12-30 V user adjustable output voltage
- Compact design and light weight (135 g)
- Fixed cord, exchangeable DC plugs available
- Available with EU, UK or AUS plug-in terminals



Tekniske data	Technical specifications	4,5-12 V	12-30 V
Inngangsspenning:	Input voltage:	200-250 VAC	
Utgangsspenning – justerbar:	Output voltage – adjustable:	4,5-12 V	12-30 V
Utg. effekt:	Output power:	Max 14.4W	Max 19,5W
Laststrøm:	Load current:	Max. 1.2A	Max. 0,65A
Lastregulering:	Load regulation:	0.5%	
Linjeregulering:	Line regulation:	0.1%	
Svitsjefrekvens, ca:	Switch frequency, approx	47kHz	
Effektforbruk, tomgang, ca:	Power consumption at idle, approx	500mW	
Temperaturområde:	Temperature range:	-10°C - +40°C.	
Ripple (typisk):	Ripple (typical):	100mVp-p	
Virkningsgrad:	Efficiency:	>80% at max output power	
Strømbegrensning:	Current limiting:	1,4A ± 0,2A	0,8A ± 0,15A
Isolasjonsklasse:	Insulation class:	II	
Isolasjonsspenning:	Insulation voltage:	3000 VAC / 4242 VDC	
Electrisk sikkerhet:	Electrical safety:	EN 60950	
EMC	EMC standards		
• Emisjon:	• Emission:	EN 61000-6-3	
• Immunitet:	• Immunity:	EN 61000-6-1	
Nettilkobling:	Mains connection:	EU, UK, AUS plug-in	
Utgangsterminaler:	Output terminals:	Sekundærkabel secondary cable	
Mål (LxBxH):	Dimensions (LxWxH):	75 x 32 x 50 mm (ex plug)	
Vekt:	Weight:	135 g	

28122007